SIDE ENTRY MODULAR PCB JACK 8P+10P PROFILE=13.10MM (FULLY SHIELDED)

SPECIFICATIONS

Insulation Resistance: 500MΩ Min.
Contact Resistance: 20mΩ Max.
Rating Current: 1.5A Max.
Rating Voltage: 120V AC.
Dielectric Voltage: 1000 Vrms 60 Sec. Min.
Temperature Range: -40ºc / +85ºc
Durability: 500 Mating cycles Min.

MATERIALS

Housing: PBT Glass Filled (UL 94V-0)
Soldering Temperature: 235ºc
Color: Black
Spring Wire: Phosphor Bronze
Gold plating Over Nickel
Shield: Brass plating Nickel Alloy
All materials must be RoHS compliant.





Recommended P.C.Board Layout MJ3E
(TOP VIEW)





Recommended P.C.Board Layout
(TOP VIEW)
MJ3F, MJ3G, MJ3H

ORDERING INFORMATION:

P/N M J $\frac{x\ x}{1}$ - $\frac{x\ x}{2}$ $\frac{x}{3}$ B

1. PANEL STOP OPTION:
   "3E" R3.05 TYPE
   "3F" F3.05 TYPE
   "3G" F3.68TYPE
   "3H" F4.57 TYPE
2. NO. OF POSITIONS & CONTACTS:
   "88" 8P8C
   "00" 10P10C
3. CONTACT FINISH:
   "A" 6 MICROINCH GOLD
   "B" 15 MICROINCH GOLD
   "C" 30 MICROINCH GOLD
   "D" 50 MICROINCH GOLD