






Buchsenleisten Raster 2,54mm / Female Header pitch 2,54mm

Serie 167




Bauhöhe 4,2mm
total height 4,2mm

Für Vierkantstift 0,64mm
und Rundstift 0,7-0,9mm
for square pin 0,64mm and
round pin 0,7-0,9mm



Raster / Pitch
2,54mm

Empfohlenes Leiterplatten Layout
Recommended P.C.B. Layout
(PCB Tolerance ±0,05)



Technische Daten / Technical Data
 Isolierkörper / Insulator
 Kontaktmaterial / Contact material
 Nennspannung / Current Voltage
 Nennstrom / Current Rating
 Temperaturbereich / Temperatur Range
 Lötwärmebeständigkeit / Resistance soldering

PPS-GF30-FR (UL94-V0)
 Brass CuZn36PB3
 250V AC
 3A
 -55°C...+125°C
 235°C (30-60 sec.)
 260°C (10 sec.)

weitere Informationen auf Anfrage / more information on request

Bestellbeispiel
How to order

Bitte ersetzen Sie X durch unten aufgeführten Code
Please replace X with coding listed below

167 0H XX X 1 X X X X

Veredelung / Plating

SF= Selektiv flash vergoldet / selective flash gold plating 25= 0,25µm selektiv vergoldet / selective gold plating
(andere Veredelungen auf Anfrage / other platings on request)

Anzahl Reihe / Number of row

1= 1-reihig / 1-row 2= 2-reihig / 2-row

Ausführung / Version

1= gerade / straight

Raster / Pitch

2= 2,54mm 3= 5,08mm 9= Sonderraster / other pitch

Polzahl / Number of contacts

003...040 (1-reihig / 1-row) 004...080 (2-reihig / 2-row)